

18 AUGUST 2026

Bramaderos Gold-Copper Project, Southern Ecuador

Drilling returns 176m gold-copper intersection outside 3.6Moz¹ resource

This result takes the mineralised footprint at the Porotillo discovery to 520m x 230m; This area, along with other recently identified mineralisation, will feed into the planned Resource update in the Dec-Quarter

Key Points

- Drill hole PTDD020 on the southern edge of Porotillo returns an extremely long intersection with strong grades:
 - 175.8m grading 0.50 g/t Au-Eq² from surface, including 58.6m at 0.66 g/t Au-Eq² from surface.
- Trenching also continues to expand the known mineralisation at Porotillo, with the combined intersection of trenches PO-5 and near-contiguous trenches PO-6 and PO-7 now 698m long at a grade of 0.52 g/t Au-Eq²
- Porotillo is one of the five deposits and prospects which comprise Bramaderos and is outside the existing resource; Along with other new areas of mineralisation, it will be included in the resource update set for the December quarter
- All 26 holes assayed in the recent drilling program at the Porotillo, Copete and Melonal prospects within Bramaderos have returned long mineralised intersections
- Assays pending prior to preparation of the 2026 Resource update include 4 more holes and 9 channels at Melonal plus 3 trenches at Porotillo
- A deep Bramaderos exploration hole into the large Limon porphyry target is currently at 387m depth and continuing to a target end-of-hole length of 1,200m.

Sunstone Managing Director Patrick Duffy said: *"We continue to expand the known mineralisation over significant areas outside the 3.6Moz resource."*

"The Porotillo discovery now measures a large area of around 550m x 240m. This will feed into the impending resource update, along with the other significant areas of mineralisation outlined by the recent highly successful drilling and trenching campaign."

"Assays are pending for four additional holes at Melonal, plus nine channels at Melonal and a further three long trenches at Porotillo before we commence the mineral resource update. These additional assay results will be received during August and early September."

"The drill rig is currently drilling a 1200m-long porphyry exploration hole at Limon targeting the deeper porphyry gold-copper system below and southwest of the shallow Limon epithermal gold-silver deposit".

ASX ANNOUNCEMENT




Figure 1: The cluster of five porphyry gold-copper systems in the Bramaderos concessions (Brama, Alba, Melonal, Copete and Porotillo), and showing the area where resource drilling in the recent drill program was undertaken at Porotillo, Copete and Melonal to grow the Bramaderos Mineral Resource. Background colour shading is gold in soils.

Sunstone Metals Ltd (ASX: STM) advises that assays from the latest two drill holes completed at the Porotillo and Copete porphyry systems have returned long intervals of gold and copper mineralisation located outside the existing 3.6 Moz AuEq Mineral Resource at the Bramaderos Project in Ecuador (Table 1).

The latest drill results bring the total number of mineralised holes drilled into the cluster of porphyry systems and located outside the current Bramaderos Mineral Resource to 26, further demonstrating the potential for resource growth beyond the existing resource envelope.

Previous intersections from the most recent drill program were reported in ASX announcements dated 14 April 2026, 4 May 2026, 14 May 2026, 21 May 2026, 2 June 2026, 2 July 2026 and 3 August 2026.

ASX ANNOUNCEMENT

1. Drilling at Porotillo and Copete

A total of 25 drill holes were completed at Copete and Porotillo during February to June 2026 for 4,776m of drilling, with assays now received for the final two holes at Porotillo and Copete (Table 1 and Figure 2).

The final drillhole PTDD020 at Porotillo intersected 175.76m grading 0.50 g/t Au-Eq² (0.32 g/t Au, 0.11% Cu) from surface. Higher-grade zones were encountered in the upper and lower parts of the hole. Mineralisation is open at depth and to the south (Table 1 and Figure 2). All bulk intersections with higher-grade sub-intervals are listed in Table 1.




Figure 2: Status of drilling at Copete and Porotillo and location of new intersections in holes PTDD020 and CPDD005 and Trench PO-7. Assays are pending for three trenches at Porotillo (PO-8, PO-9 and PO-10).

Drilling and trenching have now intersected significant mineralisation over a northwest-southeast extent of 550m and a northeast-southwest extent of up to 240m at Porotillo.

Grade shells for the mineralisation at Porotillo and Copete reveal several domains of higher-grade gold and copper mineralisation that are greater than 0.5 g/t Au-Eq² (Figure 3).

ASX ANNOUNCEMENT




Figure 3: Grade contours (>0.30, >0.35, >0.40, >0.5 g/t Au-Eq²) at Porotillo and Copete in plan view and based on assay results received to date from drillholes and surface trenches. Assays are outstanding for trenches PO-8, PO-9 and PO-10. Trenches PO-11 and PO-12 have been excavated, trench PO-13 is underway and trenches PO-14 to PO-17 are planned.




Figure 4: Tenor of bulk intersections in the 26 drill holes and 8 trenches assayed from the current program at Porotillo, Copete and Melonal relative to the Bramaderos cut-off grade (0.30 g/t Au-Eq²) and resource grade (0.50 g/t Au-Eq²). The two new drill intersections and the new trench intersection in this announcement (outlined in red) are shown.

ASX ANNOUNCEMENT

Drillhole		From (m)	To (m)	Length (m)	Au-Eq (g/t) ²	Au (g/t)	Cu (%)	Ag (g/t)	Mo (ppm)
PTDD001		0	200.55	200.55	0.42	0.25	0.10	1.30	2.87
	Includes	0	54.67	54.67	0.57	0.36	0.13	1.36	3.68
PTDD002		0	140.45	140.45	0.45	0.25	0.12	1.26	6.29
	Includes	0	60.25	60.25	0.65	0.40	0.15	1.54	2.25
PTDD003		0	150.15	150.15	0.53	0.29	0.14	1.65	7.68
	Includes	130.35	150.15	19.80	0.69	0.36	0.20	1.63	24.35
PTDD004		0	116.00	116.00	0.57	0.36	0.12	1.98	19.11
	Includes	0	91.75	91.75	0.66	0.42	0.14	2.21	19.61
	Includes	0	46.00	46.00	0.74	0.48	0.15	2.71	19.75
	and	72.00	91.75	19.75	0.91	0.66	0.15	1.77	28.07
PTDD005		24.90	124.35	99.45	0.33	0.19	0.08	1.14	2.36
	Includes	24.90	45.20	20.30	0.45	0.27	0.11	1.63	3.61
	and	66.65	85.40	18.75	0.54	0.32	0.13	1.74	3.99
	and	108.70	124.35	15.65	0.37	0.21	0.10	1.21	1.64
PTDD006		0	200	200	0.62	0.38	0.14	1.59	15.25
	Includes	0	19	19	1.01	0.77	0.15	1.76	3.05
PTDD007		0	150.73	150.73	0.54	0.34	0.12	2.09	11.56
	Includes	0	26	26	0.84	0.53	0.19	2.23	11.82
PTDD008		0	141.60	141.60	0.44	0.28	0.10	1.18	5.38
	Includes	0	45.27	45.27	0.49	0.32	0.10	1.16	2.81
	Includes	0	10.89	10.89	0.84	0.60	0.15	1.61	2.48
PTDD009		0.45	298.25	297.80	0.40	0.21	0.12	1.34	9.24
	Includes	22	77.25	55.25	0.62	0.40	0.13	2.25	4.19
PTDD010		0	202.08	202.08	0.32	0.18	0.09	1.02	20.33
	Includes	68	131.01	63.01	0.35	0.24	0.10	1.26	27.17
PTDD011		0	191.80	191.80	0.30	0.17	0.08	0.96	1.29
	Includes	21.8	96.40	74.60	0.41	0.24	0.10	1.22	1.90
PTDD012		0	213.35	213.35	0.53	0.31	0.13	1.82	6.59
	Includes	11	63	52	0.76	0.44	0.19	2.76	6.17
PTDD013		0	200.89	200.89	0.43	0.27	0.09	2.05	21.69
	Includes	43	77	34	0.84	0.64	0.11	3.48	11.42
PTDD014		0	112	112	0.51	0.30	0.12	2.01	7.67
	Includes	18.5	71.5	53	0.62	0.41	0.12	2.57	9.38
PTDD015		0	150.28	150.28	0.43	0.30	0.08	1.40	9.60
	Includes	0	77.50	77.50	0.56	0.41	0.08	1.83	9.67
PTDD016		0	128.92	128.92	0.37	0.21	0.09	1.67	5.57
	Includes	32.6	72.5	39.9	0.51	0.29	0.13	2.54	9.79
PTDD017		0	196	196	0.62	0.35	0.16	1.90	10.38
	Includes	0	143	143	0.72	0.42	0.18	2.22	11.17
	Includes	130.8	135.6	4.80	2.29	0.59	1.00	15.76	30.74
PTDD018		0	137	137	0.58	0.36	0.14	1.48	6.35
	Includes	0	95	95	0.68	0.42	0.15	1.52	4.04
PTDD019		0	15.4	15.4	0.89	0.66	0.14	1.68	4.86
	and	30.1	45.9	15.8	0.68	0.41	0.17	1.34	6.22
	and	96.6	175.3	78.7	0.51	0.34	0.10	1.26	9.86
PTDD020		0	175.76	175.76	0.50	0.32	0.11	1.31	3.04
	Includes	0	58.6	58.6	0.66	0.45	0.13	1.80	3.51
	and	102.6	175.76	73.16	0.53	0.33	0.13	1.37	3.77
CPDD001				200	0.45	0.33	0.07	1.10	9.15
	Includes			50.55	0.62	0.52	0.05	2.75	20.94
	Includes			26.90	0.75	0.65	0.04	4.38	23.11
CPDD002				162.17	0.32	0.20	0.07	0.65	6.59
	Includes			58	0.42	0.27	0.09	0.86	5.67
CPDD003		0	200	200	0.40	0.27	0.08	0.76	11.68
	Includes	0	43.75	43.75	0.58	0.41	0.10	1.02	8.49
	and	127.9	187	59.1	0.47	0.28	0.11	0.60	14.77
CPDD004		0	148.16	148.16	0.40	0.30	0.06	0.77	16.41
	Includes	0	31.45	31.45	0.49	0.38	0.06	1.04	16.51
	and	132	142.66	10.66	0.55	0.40	0.09	0.85	22.29
CPDD005		0	200.34	200.34	0.28	0.14	0.08	1.16	34.61

Table 1: Gold, copper, silver and molybdenum intersections at Porotillo and Copete (PTDD020 and CPDD005 are the most recently assayed drillholes) and complete the current phase of drilling for the Porotillo-Copete inaugural resource estimate. Assays from trenches PO-8, PO-9 and PO-10 at Porotillo are awaited.

ASX ANNOUNCEMENT

Drillhole	Prospect	Collar Location (PSAD56 Zone 17S)			Hole Orientation		
		Easting	Northing	RL	Azimuth	Dip	EOH
PTDD001	Porotillo	631641	9547810	867	322	-45	200.58
PTDD002	Porotillo	631643	9547806	867	152	-50	140.45
PTDD003	Porotillo	631543	9547846	882	155	-60	150.15
PTDD004	Porotillo	631392	9548103	851	300	-50	166.85
PTDD005	Porotillo	631543	9547856	882	315	-50	202.28
PTDD006	Porotillo	631572	9547950	863	130	-50	221.49
PTDD007	Porotillo	631392	9548103	851	120	-50	150.73
PTDD008	Porotillo	631572	9547950	863	310	-60	216.37
PTDD009	Porotillo	631341	9548060	899	300	-90	298.25
PTDD010	Porotillo	631731	9547844	816	290	-55	201.63
PTDD011	Porotillo	631543	9547846	882	245	-75	250.25
PTDD012	Porotillo	631341	9548060	899	120	-50	213.35
PTDD013	Porotillo	631531	9548087	815	262	-45	200.89
PTDD014	Porotillo	631341	9548060	899	300	-50	153.04
PTDD015	Porotillo	631531	9548087	815	135	-50	200.60
PTDD016	Porotillo	631341	9548060	899	210	-40	128.92
PTDD017	Porotillo	631572	9547950	863	95	-50	204.00
PTDD018	Porotillo	631642	9547807	861	218	-65	197.91
PTDD019	Porotillo	631572	9547950	863	38	-55	191.93
PTDD020	Porotillo	631543	9547846	882	190	-45	175.76
CPDD001	Copete	631917	9548211	879	120	-45	200
CPDD002	Copete	632062	9548118	858	300	-55	162.17
CPDD003	Copete	631957	9548181	872	225	-62	200.01
CPDD004	Copete	631957	9548181	872	30	-55	148.16
CPDD005	Copete	631927	9548044	778	300	-45	200.34

Table 2: Drill hole locations for all Sunstone assayed holes at Porotillo and Copete.

2.0 Trenching at Porotillo and Channel Sampling at Melonal

In addition to the 2026 phase of drilling at Copete, Porotillo and Melonal, Sunstone has been expanding the surface sampling program by excavating trenches and cutting channel samples from outcrops in surface ravines across all three of these porphyry centres that lie outside the November 2025 Bramaderos Mineral Resource. Table 5 summarises the status of assaying of drill holes and surface trench and channel sampling on these three porphyry centres that will be used in the 2026 Bramaderos Resource update.

The most recent trench to be assayed at Porotillo was trench PO_7, a northwest continuation of trench PO_5 that assayed 462.22m grading 0.55 g/t Au-Eq² (ASX announcement 11 March 2026). The extension trench PO_7 yielded a further 90.32m grading 0.48 g/t Au-Eq² (Table 3 and Figure 5).

Contiguous trenches PO_5, PO_6 and PO_7 now define a combined, non-linear, northwest-southeast surface intersection of 698.03m grading 0.52 g/t Au-Eq² at Porotillo.

Trench		Length (m)	Au-Eq (g/t)	Au (g/t)	Cu (%)	Ag (g/t)	Mo (ppm)
PO_7		90.32	0.48	0.32	0.10	1.25	12.01
PO-5, PO-6, PO-7	(Combined)	698.03	0.52	0.34	0.11	1.33	6.16

Table 3: Intersection for trench PO-7 and for combined contiguous trenches PO-5, PO-6 (see ASX announcements dated 11 March 2026 and 3 August 2026) and PO-7.

ASX ANNOUNCEMENT

Trench	Start			End		
	Easting	Northing	RL	Easting	Northing	RL
PO_7	631356	9548133	843	631252	9548174	844

Table 4: Trench location for PO_7.

Data for 2026 Melonal Resource upgrade and 2026 Porotillo-Copete Inaugural Resource

	Melonal		Porotillo		Copete	
Acquisition	Meterage		Meterage		Meterage	
2023	2 Drill holes (MEDD001-002)	737				
2024	4 Channels (QM-1 to QM-4)	704			1 Trench (ML-01)	279
2025	2 Channels (P6 and P7)	219	4 Trenches (PO-1 to PO-4)	203	13 Channels (QC-1 to QC-13)	720
2026	9 Channels (QM5 to QM13)	590	3 Trenches (PO-5 to PO-7)	715	5 Drill holes (CPDD001-005)	911
	1 Drill hole (MEDD003)	271	3 Trenches (PO-8 to PO-10)	558		
	4 Drill holes (MEDD004-007)	1226	19 Drill holes (PTDD001-019)	3,690		
			1 Drill hole (PTDD020)	176		

Table 5: Drill, trench and channel samples collected by Sunstone on the porphyry centres at Melonal, Porotillo and Copete during 2023-2026 (black entries are assayed, red entries are pending receipt of assays prior to the resource estimation).




Figure 5: Figure showing assayed trenches (PO-1 to PO-7 and ML-01) and channel samples at Copete and Porotillo plus rockchips across the deposits. Results for the newly assayed Trench PO-7 are shown together with the location of new trenches labelled 8-10 in yellow (PO-8, PO-9 and PO-10 all with assays pending, and trenches PO-11 and PO-12 which have just been excavated for sampling). The surface trench and channel data will contribute to the planned 2026 Bramaderos Mineral Resource Estimate that will include Porotillo, Copete and Melonal.

ASX ANNOUNCEMENT

About Sunstone Metals

Sunstone Metals Limited (“Sunstone” or “Company”) is an ASX-listed mineral exploration company with two world-class gold and copper projects in Ecuador:

1. The **Bramaderos Project**, located in Southern Ecuador, contains the November 2025 Mineral Resource estimate of 220Mt at 0.50g/t AuEq for 3.6Moz AuEq^{1,2}.

JORC Classification	Tonnage (Mt)	Au (g/t)	Cu (%)	Ag (g/t)	AuEq ¹ (g/t)	AuEq ¹ (Mozs)
Indicated	40	0.38	0.10	1.26	0.56	0.6
Inferred	190	0.32	0.10	1.14	0.49	2.9
Total	220	0.33	0.10	1.16	0.50	3.6

Additionally, the Bramaderos Project has a Porphyry Exploration Target of between 4.1Moz and 11.2Moz AuEq^{1,2} within 315 to 505Mt at a grade between 0.41 and 0.68g/t, and the Limon epithermal gold-silver Exploration Target of between 0.9 and 1.7Moz AuEq^{3,4} within 30 to 44Mt at a grade between 0.9 and 1.2g/t.

The potential quantity and grade of the Exploration Targets is conceptual in nature. There has been insufficient exploration to estimate a Resource for the reported exploration target areas. It is uncertain if further exploration will result in the estimation of a Resource.

2. The **El Palmar Project** is located in northern Ecuador, 60km north-west of Ecuador’s capital Quito. The property sits on the regionally significant Toachi Fault Zone that hosts a number of, which hosts several world-class copper porphyry systems. The Project has both at-surface and deeper porphyry gold-copper systems and an initial Mineral Resource estimate of 64Mt at 0.60g/t AuEq for 1.2Moz AuEq^{5,6}.

JORC Classification	Tonnage Mt	Average Grade					Material Content			
		AuEq ⁶ (g/t)	Au (g/t)	Ag (g/t)	Cu (ppm)	Cu (%)	AuEq ⁶ (Koz)	Au (Koz)	Ag (Koz)	Cu (Kt)
Indicated	5	0.63	0.42	0.81	1,456	0.15	100	100	100	7
Inferred	59	0.59	0.40	0.65	1,290	0.13	1,100	700	1,200	70
Total	64	0.60	0.41	0.66	1,301	0.13	1,200	800	1,300	80

Additionally, the El Palmar Project has a porphyry Exploration Target of between 15Moz and 45Moz AuEq^{5,6} within 1.0 to 1.2Bt at a grade between 0.3 - 0.7g/t gold and 0.1 – 0.3% copper.

A flyover video of the two Projects can be viewed here: [CLICK LINK](#)

Strategy

The porphyry projects at Bramaderos and El Palmar have the potential to evolve into multi-decade gold-copper mining centres. At Bramaderos, a Scoping Study has been completed which indicated project viability and large growth potential. Sunstone plans to further grow the Bramaderos resource while continuing to advance the project studies towards development. At El Palmar, Sunstone is testing the deep gold-copper targets, with drilling expected to recommence in September 2026.

Sunstone has an ongoing strategic process to determine a preferred long-term funding model to unlock the substantial value of its two world-class projects. The Company also continues to monitor and evaluate potential opportunities to continue to grow our business in Ecuador, where clear shareholder value can be demonstrated.

ASX ANNOUNCEMENT

Track Record

The team at Sunstone has been involved in significant discoveries of porphyry and epithermal copper-gold mineralisation at Tujuh Bukit in Indonesia and Cascabel in Ecuador, and the successful development of the King of the Hills Gold Mine in Western Australia and Koniambo Nickel Mine and Smelter in New Caledonia.

Excellent infrastructure

All projects are supported by established infrastructure close to power, road and port infrastructure.

Community support

The Board and Management Team take their responsibilities towards the host communities seriously and have endeavoured to uphold the highest ESG standards across our business. Sunstone published its inaugural Sustainability Report in 2023, outlining the level of support and engagement with local communities and project stakeholders.



Figure 6: Location of Sunstone's Bramaderos and El Palmar projects, Ecuador.

ASX ANNOUNCEMENT

Mr Patrick Duffy, Managing Director of Sunstone Metals Ltd., has authorised this announcement to be lodged with the ASX.

For further information, please visit www.sunstonemetals.com.au

Mr Patrick Duffy
Managing Director
Sunstone Metals Ltd
Tel: 03 7044 2627
Email: info@sunstonemetals.com.au

Media:
Paul Armstrong
Read Corporate
+61 8 9388 1474

¹ Refer ASX Announcement on 24 November 2025.

² The gold equivalent (AuEq) calculation formula for porphyry gold-copper-silver mineralisation at Bramaderos is $AuEq(g/t) = ((Au\ grade \times Au\ price \times Au\ recov / 31.1035) + (Ag\ grade \times Ag\ price \times Ag\ recov / 31.1035) + (Cu\ grade \times Cu\ price \times Cu\ recov / 100)) / (Au\ price \times Au\ recov / 31.1035)$. The prices applied were US\$1,800/oz gold, US\$4.50/lb copper and US\$22/oz silver. Recoveries are estimated at 88% for gold, 85% for copper and 60% for silver based on metallurgical studies. In Sunstone's opinion, all the elements included in the metal equivalents calculation have reasonable potential to be recovered and sold.

³ Refer ASX Announcement on 5 February 2024.

⁴ The gold equivalent calculation formula for the Limon epithermal gold-silver mineralisation is $AuEq(g/t) = Au(ppm) + (Ag(ppm)/82)$. The prices used were US\$1,800/oz gold and US\$22/oz silver. Recoveries are estimated at over 90% for gold and 90% for silver from metallurgical studies. In Sunstone's opinion all the elements included in the metal equivalents calculation have reasonable potential to be recovered and sold.

⁵ Refer ASX Announcement on 22 October 2024.

⁶ The AuEq calculation formula for porphyry gold-copper-silver mineralisation at El Palmar is $AuEq(g/t) = ((Au\ grade \times Au\ price \times Au\ recov / 31.1035) + (Ag\ grade \times Ag\ price \times Ag\ recov / 31.1035) + (Cu\ grade \times Cu\ price \times Cu\ recov / 100)) / (Au\ price \times Au\ recov / 31.1035)$. The prices applied were US\$1,800/oz gold, US\$4.50/lb copper and US\$22/oz silver. Recoveries are estimated at 90% for gold, 78% for copper (excluded for oxide material), and 60% for silver based on metallurgical studies. Grades for the Exploration Target are 0.30g/t Au and 0.10% Cu. In Sunstone's opinion, all the elements included in the metal equivalents calculation have reasonable potential to be recovered and sold.

ASX ANNOUNCEMENT

Competent Persons Statement

The information in this report that relates to exploration results and Exploration Targets is based upon information reviewed by Dr Bruce Rohrlach who is a Member of the Australasian Institute of Mining and Metallurgy. Dr Rohrlach is a full-time employee of Sunstone Metals Ltd and has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". Dr Rohrlach consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The information relating to the Bramaderos Mineral Resource is extracted from the ASX announcement on 24 November 2025. The information relating to the El Palmar Mineral Resource is extracted from the ASX announcement on 22 October 2024. The company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcements and that all material assumptions and technical parameters underpinning the estimates in the relevant market announcements continue to apply and have not materially changed. The company confirms that the form and context in which the Competent Person's findings are presented for their respective Mineral Resource estimates have not been materially modified from the original market announcements.

Information on Exploration Targets

The potential quantity and grade of the Exploration Targets is conceptual in nature. There has been insufficient exploration to estimate a Mineral Resource for the reported exploration target areas. It is uncertain if further exploration will result in the estimation of a Mineral Resource.

Bramaderos

The Bramaderos porphyry Exploration Target within the Bramaderos concession is estimated from four areas – the extensions to the Brama-Alba system that are not captured in the Mineral Resource estimate (MRE), the majority of the Melonal system that is not captured in the Mineral Resource estimate (MRE), and mineralisation drilled at the targets of Limon and Copete-Porotillo porphyry mineralisation.

The Exploration Target does not include known porphyry mineralisation at Sandia, Playas or Yeso. It was decided to not include these areas because Sunstone has not yet completed any or sufficient drilling in these areas. Further work in these areas will be undertaken and they are expected to contribute to an expanded Exploration Target in future.

Several areas of mineralisation have been identified outside of the area of the MRE. The MRE captured material that was drilled to sufficient density an economically modelled pit. Inadequate drilling exists in some areas both within and outside the modelled pit to show mineralisation continuity. Furthermore, the effect of the reasonable prospects of eventual economic extraction was to exclude 31% of material. This material has been captured in the Exploration Target.

Six domains were identified as having clear potential for additional mineralisation and these were reviewed either on a depth slice basis, or a block basis. Volumes were calculated and grade was assigned based on nearby data and on comparison with the overall Brama-Alba grade. This exploration target was reduced by the amount of material within it that was converted to resource by the latest MRE update.

The Melonal target is a continuation of the Brama-Alba system. It is geologically grouped with Brama-Alba. Recent drilling by Sunstone, and historical drilling from 2007, has confirmed that the Melonal target is mineralised, and that mineralisation is hosted in rocks the same as those drilled at the nearby Brama-Alba deposit. The mineralised rocks are coincident with a discrete sub-vertical magnetic anomaly measuring up to 400m in diameter, and with a vertical extent of over 1,000m. The Exploration Target for Melonal was considered to a depth of 500m. The Melonal target straddles the approved Bramaderos-01 and Bramaderos-02 concessions. This exploration target was reduced by the amount of material within it that was converted to resource by the latest MRE update.

ASX ANNOUNCEMENT

Sunstone has drilled 8 effective diamond holes at the Limon porphyry target. Mineralisation has been intersected in a number of holes. A trench (LM_TR_01) was completed at Limon prior to drilling in an area of outcropping stockwork veining and minor secondary copper mineralisation. It returned 97m at 0.73g/t gold and 0.23% copper. A recent hole drilled under the trench has intersected similar stockwork veined intrusive and contains chalcopyrite.

This area around Trench TR_LM_01 has been included in the porphyry Exploration Target where more drilling is required to allow inclusion in a Mineral Resource estimate. This target area will be further explored with drilling programs to be executed over the next two years, subject to the Company's funding ability.

Copete and Porotillo

The Copete and Porotillo exploration targets are areas of outcropping porphyry stockwork veining that occur within an extensive gold and copper soil geochemical anomaly. These areas have seen substantial historical drilling (13 drill holes) with extensive mineralised intersections, plus widespread rockchip sampling of surface mineralisation, channel sampling in ravines and an extensive mineralised trench ML-01 at Copete that assayed 214m @ 0.50 g/t AuEq² (ASX announcement 12 November 2024).

At Porotillo, within the main body of the gold-in-soil geochemical anomaly, an extensive early-mineral quartz diorite intrusion hosts overprinting porphyry-related, disseminated and vein stockwork mineralisation over an area spanning up to approximately 530m by 310m. Very substantial historic drill intersections were encountered at Porotillo.

Two domains were modelled to generate the Copete-Porotillo exploration target to depths of 200m and 400m below surface.

This target area will be further explored with drilling programs to be executed over the next two years, subject to the Company's funding ability.

Limon epithermal

The Limon epithermal Exploration Target was estimated on target prospects where there was a combination of diamond drilling (by Sunstone), geological mapping, trenching, geochemistry (soils) and to a lesser extent geophysical data (magnetics) which could support the geological and mineralisation concept model.

The Limon alteration area has been covered with soil sampling on a 50m x 50m grid. This survey is an important exploration method which identified several gold-in soil anomalies that are primary targets for drilling. The soil geochemical data is further interpreted using related element associations typical of epithermal systems, such as areas of somewhat coincident gold, silver, zinc, lead, copper, tellurium and arsenic. Target areas have also been strengthened using alteration mineralogy from a hand-held Terraspec instrument. These data assist in mapping the alteration zones most likely to be associated with epithermal mineralisation.

Drilling at Limon has also intersected an intermediate sulphidation epithermal system in numerous drill holes including LMDD017, 26, 30, 32, 38, 40, 43 and 46-51. Drill intersections include 185m @ 2.85 g/t AuEq⁴ (include 31m @ 12.93 g/t AuEq⁴) in LMDD026, and 269m @ 1.05 g/t AuEq⁴ (include 11m @ 14.15 g/t Au) in LMDD040.

Standard geological mapping and rock chip sampling has also been undertaken across the Limon target area.

The volume ranges for the initial Exploration Target in the Central Shoot were estimated using cross sections and 3-D modelling in Leapfrog software, based on drilling, mineralised rock types, grade distribution, potential for extrapolating mineralisation continuity, and interpreted geological risk.

The volume ranges for the other components were estimated from geological interpretation and guided by the extent of surface geochemical anomalism, supplemented by preliminary drilling. A conservative approach was taken to the potential distribution of gold and silver-bearing veins.

This target area will be further explored with drilling programs to be executed over the next year, subject to the Company's funding ability.

ASX ANNOUNCEMENT

El Palmar

The Exploration Target within the El Palmar concession is estimated from within the T1, T2 and T3 areas.

The Exploration Target does not include interpreted or known porphyry mineralisation at the T4 and T5 target areas. It was decided not to include these areas because Sunstone has not yet completed any drilling at T4 and has conducted only minor drilling at T5. Further work in these areas will be undertaken and they are expected to contribute to an expanded Exploration Target in future.

The components of the exploration target are based on a combination of diamond drilling conducted by Codelco (during 2012) and by Sunstone (during 2022 and 2023), ground magnetics, multi-element soil sampling, multi-element rock chip and channel sampling, multi-element trench sampling and deep magnetic inversion anomalies modelled from ground magnetic data.

Wireframes of domains within the Exploration Target areas were created in Leapfrog software using data interpreted from the Mineral Resource block model, iso-surface contours of modelled magnetic intensities, and grade ranges in available diamond drill holes. The volumes were multiplied by a specific gravity of 2.72g/cc (the average density of the T1 resource) to determine the tonnage range of the target. Grade ranges were determined with reference to drill intersections and surface rock chip assays.

The next step in testing these targets is primarily diamond drill testing. The targets have been adequately defined, but drill programs still require further detailed planning regarding the number of drill holes, their azimuths, dips, and final depths. Drilling of these targets will be undertaken over the next two years, subject to the company's funding availability.

ASX ANNOUNCEMENT

TABLE 1 – Section 1: Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as downhole gamma sondes, or handheld XRF instruments, etc.). These examples should not be taken as limiting the broad meaning of sampling.	The new results announced here are from diamond drilling samples. The drill core sampling was carried out using half core, generally at 1- 2 m intervals.
	Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.	Core recovery was good, and core aligned prior to splitting.
	Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done, this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases, more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information.	Diamond drill, rock chip and channel sampling points have been guided by geological mapping. The drill samples from Copete were dried, crushed to 70% passing 2mm, split 1000 g, and pulverised to 85% passing 75 microns. A 20g portion of this sample was used for multi-element analysis (IMS-230) and a 30g sample for Fire Assay Au (FAS-111).
Drilling techniques	Drill type (e.g., core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Current drilling by Sunstone is diamond core drilling, similar to prior drilling at the Bramaderos project. It comprises diamond core drilling and has drilled to various depths up to 1200m. The diamond core was drilled, delivering either HTW (70.9mm) or NTW (56mm) core. Drill core is oriented using a Reflex ACT II tool for bottom of hole.
Drill sample recovery	Method of recording and assessing core and chip sample recoveries and results assessed.	Diamond core recovery data for Copete drilling was measured for each drill run and captured in a digital logging software package. The data has been reviewed and core recovery was approximately 100% throughout.
	Measures taken to maximise sample recovery and ensure representative nature of the samples.	Core recovery at Copete was good; no extra measures were taken to maximise sample recovery.
	Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	No relationship between sample recovery and grade has been established.
Logging	Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	Drill samples, trench samples and rock chips were logged for lithology, weathering, structure, mineralogy, mineralisation, colour, and other features. Logging and sampling were carried out according to Sunstone's internal protocols and QAQC procedures which comply with industry standards.
	Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography.	Drill samples, trench samples, channel samples and rock chips are logged for lithology, weathering, structure, mineralogy, mineralisation, colour, and other features.
	The total length and percentage of the relevant intersections logged.	The drill holes, plus trench and channel samples, are logged in full, from start to finish of the excavation.
Sub-sampling techniques and sample preparation	If core, whether cut or sawn and whether quarter, half or all core taken.	Half core was used to provide the samples that were submitted for assay. Quarter core samples were taken ~1 in every 28 samples for duplicate sampling. The remaining core is left in the core trays.
	If non-core, whether riffled, tube sampled, rotary split, etc. and whether sampled wet or dry.	N/A.
	For all sample types, the nature, quality and appropriateness of the sample preparation technique.	Surface and drill core samples from Copete were sent to the LAC y Asociados Cia. Ltda. Sample Preparation

ASX ANNOUNCEMENT

Criteria	JORC Code explanation	Commentary
		Facility in Cuenca, Ecuador. The standard sample preparation for drill core, trench, and channel samples (Code PRP-910) is: drying the sample, crushing to a size fraction of 70% <2mm, and splitting the sample to a 250g portion using a riffle or Boyd rotary splitter. The 250g sample is then pulverised to >85% passing 75 microns and then split into two 50g pulp samples. Then one of the pulp samples was sent to the MS Analytical Laboratory in Vancouver (Unit 1, 20120 102nd Avenue, Langley, BC V1M 4B4, Canada) for gold and base metal analysis. The sample preparation is carried out according to industry standard practices using highly appropriate sample preparation techniques.
	Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.	- Sunstone used an industry standard QAQC programme involving Certified Reference Materials "standards" and blank samples, which were introduced in the assay batches. - Standards (Certified Reference Materials) or analytical blanks were submitted at a rate of 1 in 28 samples. Field duplicates were also taken at a rate of approximately 1 in 28 samples. - The check or duplicate assay results are reported along with the sample assay values in the final analysis report.
	Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling.	- For diamond core, the routine sample procedure is to always take the half/quarter core to the right of the orientation line (looking down hole) or the cut line (in cases where the orientation line was not reliable). - Once assay results are received, the results from duplicate samples are compared with the corresponding routine sample to ascertain whether the sampling is representative.
	Whether sample sizes are appropriate to the grain size of the material being sampled.	Sample sizes are considered to be appropriate for the style of sampling undertaken and the grain size of the material, and correctly represent the style and type of mineralisation at the exploration stage.
Quality of assay data and laboratory tests	The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.	- Sunstone uses a fire assay gold technique for Au assays (FAS-111) and a four acid multi-element technique (IMS-230) for a suite of 48 elements. FAS-111 involves Au by Fire Assay on a 30-gram aliquot, fusion and atomic absorption spectroscopy (AAS) at trace levels. IMS-20 is considered a near total 4 acid technique using a 20g aliquot followed by multi-element analysis by ICP-AES/MS at ultra-trace levels. - This analysis technique is considered suitable for this style of mineralisation.
	For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis, including instrument make and model, reading times, calibration factors applied and their derivation, etc.	Handheld XRF data, together with detailed geological logging, are used as a guide to areas of potential mineralisation in drillholes and samples from these areas are sent for laboratory analysis as described above.
	Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.	- Standards, blanks and duplicates are inserted ~1/28 samples. The values of the standards range from low to high grades and are considered appropriate for monitoring performance near the cut-off and near the deposit's mean grade. - The check sampling results are monitored, and performance issues are communicated to the laboratory if necessary.

ASX ANNOUNCEMENT

Criteria	JORC Code explanation	Commentary																				
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Procedure checks have been completed by the Competent Person for exploration results for this announcement.																				
	<i>The use of twinned holes.</i>	Twin holes have not been drilled in these areas.																				
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	Sunstone sampling data were imported and validated using Excel.																				
	<i>Discuss any adjustments to assay data.</i>	Assay data were not adjusted. Core loss intervals are assigned assay values of zero where present.																				
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	Sample co-ordinates are located by DGPS, and for trench samples, are measured along the length of the trench.																				
	<i>Specification of the grid system used.</i>	Ecuador projection parameters:<table><tr><th>Parameter</th><th>Value</th></tr><tr><td>Reference Ellipsoid</td><td>International 1924</td></tr><tr><td>Semi Major Axis</td><td></td></tr><tr><td>Inverse Flattening (1/f)</td><td></td></tr><tr><td>Type of Projection</td><td>UTM Zone -17S (Datum PSAD56)</td></tr><tr><td>Central Meridian:</td><td>-81.0000</td></tr><tr><td>Latitude of Origin</td><td>0.0000</td></tr><tr><td>Scale on Central Meridian</td><td>0.9996</td></tr><tr><td>False Northing</td><td>10000000</td></tr><tr><td>False Easting</td><td>500000</td></tr></table>	Parameter	Value	Reference Ellipsoid	International 1924	Semi Major Axis		Inverse Flattening (1/f)		Type of Projection	UTM Zone -17S (Datum PSAD56)	Central Meridian:	-81.0000	Latitude of Origin	0.0000	Scale on Central Meridian	0.9996	False Northing	10000000	False Easting	500000
	Parameter	Value																				
	Reference Ellipsoid	International 1924																				
Semi Major Axis																						
Inverse Flattening (1/f)																						
Type of Projection	UTM Zone -17S (Datum PSAD56)																					
Central Meridian:	-81.0000																					
Latitude of Origin	0.0000																					
Scale on Central Meridian	0.9996																					
False Northing	10000000																					
False Easting	500000																					
<i>Quality and adequacy of topographic control.</i>	The topographic control was compared against published maps and satellite imagery and found to be of good quality.																					
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	The drill core samples were collected from diamond drill holes from the Copete target, and with sample lengths generally ranging between 1.0 and 2.0 m.																				
	<i>Whether the data spacing, and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	The data from these samples do not contribute to any resource estimate nor imply any grade continuity.																				
	<i>Whether sample compositing has been applied.</i>	No sample compositing was done.																				
Orientation of data in relation to geological structure	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	- Drilling orientations were appropriate for the interpreted geology providing representative samples. - Trench, channel orientations and rock chip locations were appropriate for the interpreted geology providing representative samples.																				
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	No sampling bias is expected at this stage.																				
Sample security	<i>The measures taken to ensure sample security.</i>	- Sunstone sampling procedures indicate individual samples were given due attention. - Sample security was managed through sealed individual samples and sealed bags of multiple samples for secure delivery to the laboratory by permanent staff of the joint venture. - MS Analytical is an internationally accredited																				

ASX ANNOUNCEMENT

Criteria	JORC Code explanation	Commentary
		laboratory that has all its internal procedures heavily scrutinised in order to maintain its accreditation. MS Analytical is accredited to ISO/IEC 17025 2005 Accredited Methods.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	- Sunstone's sampling techniques and data have been audited multiple times by independent mining consultants during various project assessments. These audits have concluded that the sampling techniques and data management are to industry standards. - All historical data has been validated to the best degree possible and migrated into a database.

TABLE 1 – Section 2: Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	The Bramaderos Exploration Concession is located in the Loja Province of southern Ecuador. The concession was granted to La Plata Minerales S.A. ("PLAMIN") in January 2017. PLAMIN is a subsidiary of Sunstone Metals Ltd. The concession is subject to a Joint Venture between Jiangxi Copper (12.5%) and Sunstone Metals Ltd. (87.5%). There are no declared wilderness areas or national parks within or adjoining the concession area. There are no established native title interests.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	The Bramaderos Exploration Concession was granted to La Plata Minerales S.A. ("PLAMIN") in January 2017. PLAMIN is now a subsidiary of Sunstone Metals Ltd. The Bramaderos Concession is subject to a Joint Venture between Sunstone Metals and Jiangxi Copper. Sunstone has an 87.5% interest in the JV. Jiangxi Copper's 12.5% interest is loan carried.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	The historic exploration at Bramaderos was completed by various groups over the period 1970-1984, 2001-2002 and 2004-2007. Most of the readily available historical data has been acquired and compiled into databases and a GIS project. Exploration by other parties has included stream sediment surveys, geological mapping, rock chip sampling (888 samples), grid-based soil sampling (1324 samples), trenching and channel sampling (17 trenches), ground magnetic surveys (31 line kilometres), electrical IP surveys, and diamond drilling (10426m).
Geology	Deposit type, geological setting and style of mineralisation.	The deposit style being explored for includes intrusion-related and stockwork-hosted porphyry gold-copper systems plus epithermal gold-silver-polymetallic veins. The setting at the Bramaderos project is a volcanic arc setting of Cretaceous-age intrusions.
Drill hole Information	- A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: a. easting and northing of the drill hole collar b. elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar c. dip and azimuth of the hole d. downhole length and interception depth e. hole length.	- Details of the samples discussed in this announcement are in the body of the text. - See Figures 1, 2, 3, 4 and 5 for the location of drilling activities, trench, channel and rockchip sampling, and soil survey coverage at Porotillo and nearby areas.
	If the exclusion of this information is justified on the	Information included in the announcement.

ASX ANNOUNCEMENT

Criteria	JORC Code explanation	Commentary
	<i>basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i>	
Data aggregation methods	In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.	- Weighted averages were calculated over reported intervals according to sample length. - No grade cut-offs were applied.
	Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated, and some typical examples of such aggregations should be shown in detail.	No aggregating of intervals undertaken at this stage.
	The assumptions used for any reporting of metal equivalent values should be clearly stated.	Preliminary metallurgical studies indicate a standard grind with a flotation circuit. Stage one will recover copper and the majority of gold as a saleable concentrate. Stage two is a finer grind with a cyanide leach for gold on site. Currently, overall estimated recoveries for the combined process are 86% for copper and 89% for gold.
Relationship between mineralisation widths and intercept lengths	If the geometry of the mineralisation with respect to the drill-hole angle is known, its nature should be reported.	Figures 1, 2, 3, 4 and 5 show the interpreted strike orientation of the mineralised lodes based on mapping and interpretation of detailed magnetic data.
	If it is not known and only the downhole lengths are reported, there should be a clear statement to this effect (e.g. 'downhole length, true width not known').	True widths of mineralised lodes are not known at this stage.
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to, a plan view of drill hole collar locations and appropriate sectional views.	See Figures 1, 2, 3, 4 and 5 for maps showing the distribution of samples.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practised to avoid misleading reporting of Exploration Results.	Figures 1, 2, 3, 4 and 5 show the current interpretations of geology.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported) including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	Figures 1, 2, 3, 4 and 5 above show various datasets that are being used to identify target areas and to guide current and future drilling.
Further work	The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling).	The planned exploration program is outlined in the announcement.
	Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.	See Figures 1, 2, 3, 4 and 5 which show areas for further exploration.