Ballymore Resources Limited
ABN 72 632 893 611
Suite 606, Level 6
10 Market Street
Brisbane, Queensland 4000

E: info@ballymoreres.com
T: +61 7 3212 6299
www.ballymoreres.com
ASX: BMR

For personal use only

ASX Release | 13 October 2026

Ruddygore Project: Torpy's discovery delivers further high-grade silver-lead-zinc from just 12m.

Highlights:

- **Further shallow high-grade polymetallic mineralisation**: BTPRC022 intersected 16m at 36.5 g/t silver (Ag), 1.3% lead (Pb), 2.4% zinc (Zn) and 2.5 g/t indium (In) from just 12m downhole.
- **Exceptional high-grade intervals within broader zone**: Including 1m at 207.7 g/t Ag, 9.9% Pb, 12.5% Zn and 5.3 g/t In from 16m, and 2m at 105.9 g/t Ag, 3.8% Pb, 9.6% Zn and 14.5 g/t In from 21m in BTPRC022.
- **Further silver-rich mineralisation**: BTPRC023 returned 11m at 49.1 g/t Ag, 1.1% Pb, 0.7% Zn and 1.6 g/t In from 54m, including 4m at 127.1 g/t Ag, 2.6% Pb, 1.5% Zn and 3.8 g/t In.
- **Updated 3D geological model has identified exciting extension possibilities**: Final assays from Torpy's holes BTPRC022–026 have been incorporated into the Torpy's 3D model, helping refine the geometry of the mineralised zones and identify additional targets for follow-up drilling.
- **Little Torpy's provides a further near-term exploration catalyst**: Assay results remain outstanding for five holes, BTPRC027–031, drilled approximately 600m south of Torpy's, several of which recorded strong visual galena and sphalerite mineralisation.
- **Further drilling planned**: Ballymore is refining its geological interpretation and advancing preparations for additional exploration and drilling across the Ruddygore Project.

Ballymore Resources Limited (ASX: BMR) has reported further high-grade silver-lead-zinc-indium results from its Torpy's discovery within the Ruddygore Project in North Queensland, extending the zone of shallow mineralisation in this emerging polymetallic system.

Final assays from five reverse circulation (RC) drill holes, BTPRC022–026, include a significant 16m mineralised intersection from just 12m downhole, containing grades of up to **207.7g/t silver, 9.9% lead and 12.5% zinc over 1m**. The results build on previously reported up-dip extensions and have been incorporated into an updated 3D geological model to improve Ballymore's understanding of the distribution and geometry of the higher-grade mineralised zones.

Ballymore Managing Director, Mr David A-Izzeddin, said:

"We're encouraged by the latest results from Torpy's, particularly the shallow high-grade intersection in BTPRC022, which returned significant silver, lead, zinc and indium grades from just 12m downhole.

Following our previous success in extending mineralisation approximately 30m up-dip, these latest intersections confirm shallow extensions to the discovery and add further geological information to guide our exploration.

Importantly, we are now developing a much clearer picture of the mineralised system. Our updated 3D model is highlighting higher-grade silver-lead-zinc shoots within a broader mineralised envelope, together with several additional prospective zones that warrant further investigation. Further drilling will be conducted to confirm the continuity and extent of these higher-grade zones".

"We also have results pending from Little Torpy's, just 600m to the south, where several drill holes encountered encouraging visible sulphide mineralisation. With further targets being evaluated across Ruddygore, we believe there is considerable scope to rapidly increase the scale of this emerging polymetallic discovery."




Figure 1 *– Cross section of the Torpy's, looking northeast, showing significant drill results to date and modelled silver grade shells (i.e. 10 g/t and 30 g/t shells).*

High-grade polymetallic mineralisation from just 12m

BTPRC022 tested the up-dip extent of mineralisation near the historic Torpy's mine workings and returned a significant shallow intersection:

BTPRC022 **16m at 36.5g/t Ag, 1.3% Pb, 2.4% Zn and 2.5g/t In from 12m including**

5m at 61.0g/t Ag, 2.3% Pb, 2.9% Zn and 1.6g/t In from 12m and

1m at 207.7g/t Ag, 9.9% Pb, 12.5% Zn and 5.3g/t In from 16m and

2m at 105.9g/t Ag, 3.8% Pb, 9.6% Zn and 14.5g/t In from 21m

This result follows previously reported drilling that extended mineralisation approximately 30m up-dip and provides further evidence of high-grade silver-lead-zinc-indium mineralisation at shallow downhole depths.

For personal use only

The higher-grade sub-intervals within BTPRC022 also demonstrate the variable distribution of silver, lead, zinc and indium within the broader mineralised interval.

Further geological interpretation is required to establish the relationship between this intersection, the historic mine workings and mineralisation identified in previous drilling.

Deeper drilling returns further silver-rich mineralisation

BTPRC023 intersected a notable silver-rich interval beneath the area tested by earlier drilling:

BTPRC023 **11m at 49.1g/t Ag, 1.1% Pb, 0.7% Zn and 1.6g/t In from 54m including**
4m at 127.1g/t Ag, 2.6% Pb, 1.5% Zn and 3.8g/t In from 55m including
3m at 162.7g/t Ag, 3.3% Pb, 1.7% Zn and 4.7g/t In from 55m

The results confirm further silver-rich mineralisation at depth, with elevated lead and indium grades within the higher-grade portion of the intersection.

Other results from the deeper holes were more variable:

- **BTPRC024**: returned 9m at 14.6 g/t Ag, 0.4% Pb, 0.3% Zn and 0.5 g/t In from 87m, including 2m at 26.5 g/t Ag and 0.8% Pb from 89m.
- **BTPRC025**: returned isolated, lower-grade intervals.
- **BTPRC026**: returned a zinc-rich interval of BTPRC026: returned a silver-zinc rich interval of 9m @ 1.42 g/t Ag and 0.3% Zn from 84m, including 1m at 5.5 g/t Ag and 0.7% Zn from 86m.

These results provide additional information on the distribution of mineralisation and will assist in refining the geological interpretation. Further drilling will be required to establish the continuity and extent of the higher-grade zones.

Updated Torpy's 3D model supports coherent mineralised system

Ballymore has updated its 3D geological model using drill hole lithology, alteration, visual estimates of mineralisation and the latest assay results from BTPRC022–026 as well as modelled geophysics datasets.

The updated interpretation highlights higher-grade silver-bearing shoots within a broader envelope of lower-grade silver-lead-zinc mineralisation. It also identifies several sub-parallel zones to the east, west and up-dip of the main mineralised zone.

These additional zones may represent peripheral intersections of separate mineralised shoots. Further drilling will be required to determine their geometry, continuity and relationship to the principal mineralised zone.

The updated model provides a framework for integrating the latest drilling with historical mine information and prioritising follow-up exploration.

For personal use only




Figure 2 *– Plan view of the Torpy's area with locations of drilling completed by Ballymore to date.*

Little Torpy's pending assays provide potential exploration catalyst

Ballymore is awaiting assay results from five RC drill holes, BTPRC027–031, completed at Little Torpy's, approximately 600m south of the main Torpy's discovery.

Several of the outstanding holes contained significant visual estimates of galena and sphalerite during drilling, including:

BTPRC030: **22m containing 4% galena and 5% sphalerite from 34m[1], including:**
11m containing 8% galena and 9% sphalerite from 42m[1]

BTPRC031: **10m containing 6% galena and 8% sphalerite from 66m[1], including:**
3m containing 15% galena and 20% sphalerite from 68m[1]

These visual estimates are preliminary geological observations and should not be considered a substitute for laboratory assays or as an indication of actual metal grades.

The outstanding results will be assessed alongside the completed Torpy's assays to refine the interpretation of the current drilling campaign and prioritise follow-up targets.

[1] Refer to ASX Announcement "Torpy's Discovery Continues to Grow as Drilling, Gravity Survey and Field Work Deliver" dated 3 July 2026

For personal use only

Next Steps

Ballymore will continue to integrate the latest assays with historical mine information, previous drilling and ongoing geological interpretation to refine its understanding of the Torpy's mineralised system.

Key areas of focus include:

- Assessing the geometry and continuity of the shallow up-dip mineralisation near the historic mine workings.
- Refining the interpretation of higher-grade silver-lead-zinc-indium shoots and their relationship to the broader mineralised envelope.
- Evaluating additional sub-parallel mineralised zones identified in the updated 3D model.
- Reviewing the outstanding Little Torpy's assays and prioritising further exploration targets across the broader Ruddygore Project.

The Company is progressing preparations for further drilling before the end of 2026, subject to final target selection and operational planning.

About Ruddygore Project

The Ruddygore Project is located adjacent to the town of Chillagoe in North Queensland and approximately 150km west of Cairns. It covers an area of 556km^2. Chillagoe was a significant mining and smelting centre that was most active from 1888 to 1927, prior to further substantial production of gold, copper and silver from the Red Dome mine from 1986 to 1997.

The Ruddygore Project hosts a range of different deposit styles including porphyry copper-gold deposits (e.g., Ruddygore), skarn-hosted copper-gold-lead-zinc skarn deposits (e.g., Red Dome, Mungana, Maniopota), sediment-hosted massive sulphide lead-zinc-silver deposits (e.g., Torpy's), tungsten-molybdenum greisen deposits (Scardon's Top Camp & Bottom Camp) and other intrusive-related gold system (IRGS) deposits.

Despite its location within a historically significant mining district, large areas of the Project remain poorly explored by modern exploration methods.

Ballymore is systematically applying modern geophysical, geochemical and drilling techniques across Ruddygore to test historic mines, known mineralisation and newly generated targets, with the objective of discovering and delineating significant gold and base metal deposits.

Planned Activities

The Company has substantial work programs planned, including:

- October 2026 Receive remaining Little Torpy's drill assay results
- October 2026 Model final Ruddygore gravity data
- October 2026 Model final Dittmer MT survey data
- October 2026 Commence Torpy's Drone magnetic survey
- Q4 2026 Dittmer bulk sample recovery

For personal use only

- Q1 2027 Complete development of the upgraded 4 level access at Dittmer.
- Q1 2027 Commence Stage 6 drill program from newly developed southern exploration drive

Approved by the Board of Ballymore Resources Limited.

For further information:

David A-Izzeddin
Managing Director
daizzeddin@ballymoreres.com

Gareth Quinn
Media and Investor Relations
gareth@republicir.com.au
0417 711 108

Competent Persons Statement

The information in this announcement that relates to Exploration Results is based on, and fairly represents, information compiled or reviewed by Mr David A-Izzeddin. Mr A-Izzeddin is a Member of The Australian Institute of Geoscientists and is a Director and an employee of the Company. Mr A-Izzeddin has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr A-Izzeddin consents to the inclusion in the announcement of the matters based on his information in the form and context in which it applies.

Forward-Looking Statements


Certain statements made during or in connection with this statement contain or comprise certain forward-looking statements regarding the Company's Mineral Resources, exploration operations and other economic performance and financial conditions as well as general market outlook. Although the Company believes that the expectations reflected in such forward-looking statements are reasonable, such expectations are only predictions and are subject to inherent risks and uncertainties which could cause actual values, results, performance or achievements to differ materially from those expressed, implied or projected in any forward-looking statements and no assurance can be given that such expectations will prove to have been correct.

Accordingly, results could differ materially from those set out in the forward-looking statements as a result of, among other factors, changes in economic and market conditions, delays or changes in project development, success of business and operating initiatives, changes in the regulatory environment and other government actions, fluctuations in commodity prices and exchange rates and business and operational risk management. Except for statutory liability which cannot be excluded, each of the Company, its officers, employees and advisors expressly disclaim any responsibility for the accuracy or completeness of the material contained in this statement and excludes all liability whatsoever (including in negligence) for any loss or damage which may be suffered by any person as a consequence of any information in this statement or any error or omission. The Company undertakes no obligation to update publicly or release any revisions to these forward-looking statements to reflect events or circumstances after today's date or to reflect the occurrence of unanticipated events other than required by the Corporations Act and ASX Listing Rules. Accordingly, you should not place undue reliance on any forward-looking statement.

For personal use only

Ballymore Resources: Unlocking Queensland's gold and base metals potential.

Ballymore Resources **(ASX:BMR)** is a Queensland-focused exploration and development company advancing a portfolio of gold and base metals projects in some of the state's most prolific mineral belts. The Company's flagship Dittmer Project, located near Proserpine, hosts the historic high-grade Dittmer gold mine and is emerging as a broader gold-copper growth story, with drilling confirming a repeat of the Duffer Lode and ongoing work aimed at supporting a maiden Mineral Resource Estimate. Ballymore also holds the Ruddygore, Ravenswood and Mount Molloy projects, providing exposure to multiple advanced exploration targets across gold, silver, copper, lead and zinc. With two granted Mining Leases, a large Queensland tenement position and an experienced team with a strong discovery and development track record, Ballymore offers investors leveraged exposure to near-term exploration catalysts and the potential reactivation of a historically high-grade mining asset.



For personal use only

APPENDIX 1. RUDDYGORE – JORC CODE TABLE 1 CHECKLIST OF ASSESSMENT AND REPORTING CRITERIA

Sampling Techniques and Data

CRITERIA	JORC Code Explanation	Commentary
SAMPLING TECHNIQUES	Nature and quality of sampling (e.g., cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.	Exploration has been undertaken at the Project since the early 1900s. Sampling methods have included surface rock chip and trenching, channel samples taken from underground exposures, soil, and stream sediment samples, together with drill hole samples comprising open hole percussion, RC percussion, and diamond core samples. Geochemistry from soil and stream sediment samples is used semi-quantitatively to guide further exploration and is not used for Mineral Resource estimation. The accuracy of rock chip geochemistry is generally high but these samples are spot samples and generally not used in Mineral Resource estimation. The accuracy of trench and channel geochemistry is generally high. These samples are regularly used in Mineral Resource estimation. The quality of open hole percussion drilling is generally low because there is a likelihood of contamination of samples. Consequently, these samples are generally used to guide further exploration and are not used for Mineral Resource estimation. The quality of RC percussion drilling is generally medium – high because the method significantly reduces the potential of contamination, unless there is a lot of groundwater or badly broken ground. Consequently, these samples can be representative of the interval drilled and can be used for Mineral Resource estimation. The quality of diamond coring is generally medium – high because the method is designed to sample the rock mass effectively in most conditions. Consequently, these samples can be representative of the interval drilled and can be used for Mineral Resource estimation. Ballymore stream sediment samples collected were screened to -80# with a 150 g sample collected. Soil samples were collected on a grid pattern. The top 10 cm of cover material was removed and regolith was sieved to -80# with a 150 g sample collected. Rock chip samples were collected from outcrop, subcrop, float material, as well as mullock samples. Ballymore completed a SkyTEM helicopter-borne, time-domain EM survey at Ruddygore. A total of 567.47 line-kms of AEM were flown at 200m spacing in a NE-SW orientation. The SkyTEM312HP system uniquely acquires at transmitter frequencies as low as 12.5Hz, using a high-power square wave form for enhanced resolution, a wide transmitter pulse width for greater target energisation, and long transmitter OFF times for imaging deep and conductive targets. Ballymore completed a semi-regional ground-based gravity survey over a 32-km corridor from south of Chillagoe to Torpy's in 2026, comprising 1,948 gravity stations.
	Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.	No information is available documenting measures to ensure sample representativity for surface sampling methods collected prior to Ballymore. These methods are not used for Mineral Resource estimation. Ballymore collected field duplicates during its soil sampling program to monitor sample representivity. Trench and channel sampling is an established method designed to deliver a representative sample of the interval being sampled.

personal use only

CRITERIA	JORC Code Explanation	Commentary
		RC drilling is an established method designed to minimise drilling-induced contamination of samples, aimed to deliver a representative sample of the interval being drilled. Diamond drilling is also an established method aimed at collecting representative samples of the interval being drilled.
	Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g., 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases, more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g., submarine nodules) may warrant disclosure of detailed information.	Economic gold mineralisation is measured in terms of parts per million and therefore rigorous sampling techniques must be adopted to ensure quantitative, precise measurements of gold concentration. If gold is present as medium – coarse grains, the entire sampling, sub-sampling, and analytical process must be more stringent. Where the main mineralisation is copper, this is measured as a percentage and therefore sampling techniques can be somewhat less rigorous than for gold. At Ruddygore, the main target is copper (Ruddygore Prospect) and silver-lead-zinc-copper-gold (Maniopota and Torpy's Crooked Creek Prospect). Procedures used to manage sampling issues are documented elsewhere in relevant sub-sections of this table.
DRILLING TECHNIQUES	Drill type (e.g., core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g., core diameter, triple or standard tube, depth of diamond tails, face-sampling bit, or other type, whether core is oriented and if so, by what method, etc).	A number of drilling programs have been recorded across the Project area. Ballymore had not completed any drilling on the Project at the time of the rock chip sampling. Most drilling was reported to be diamond but is inconsistently documented. Between 1959 and 1995 a total of 54 diamond and percussion drill holes have been completed within the Ruddygore Project area for 4,138.6m. Drilling has focussed on the Ruddygore mine area (26 holes for 1,631m), Maniopota (14 holes for 1,059m), Torpy's Crooked Creek (2 holes for 421.6m) and Metal Creek (12 holes for 1,027m). Ballymore completed six RC / diamond drillholes for 1,799.92m including 621.4m of 5¼" RC and 1,178.52m of HQ triple tube size in 2022. All holes were oriented using an Ace instrument. Ballymore has completed 31 RC / diamond drillholes for 3,932.6m at Torpy's Crooked Creek in 2025/26 including 30 RC holes for 3,770m of 5¼" RC and 1 HQ3 diameter diamond hole for 162.6m. All holes were oriented using an Ace instrument.
DRILL SAMPLE RECOVERY	Method of recording and assessing core and chip sample recoveries and results assessed.	For most programs, no information is available documenting if sample recovery was routinely recorded. MIM (1960) reported core recoveries of typically >95% at Ruddygore, as did Le Nickel (1977) at Torpy's Crooked Creek. No assessment of sample recovery has been made for historic drilling. Sample recovery for Ballymore diamond drilling in 2022 was measured on a per-run basis and generally reported to be greater than 99%. Sample recovery for the Torpy's RC / DD drilling has achieved >95% recovery will drilling stopped if samples become wet.
	Measures taken to maximise sample recovery and ensure representative nature of the samples.	No information is available documenting measures to maximise sample recovery or ensure collection of representative samples. Ballymore has utilised triple tube for diamond drilling to maximise recovery.
	Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	No assessment has been completed to determine if there is a relationship between sample recovery and grade, and whether there is any potential for sample bias associated with the drilling used to date.

personal use only

CRITERIA	JORC Code Explanation	Commentary
LOGGING	Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	Most historic drill logs document logging for lithology, structure, alteration, mineralisation, and veining. No core photography is available. Logging information for historic drilling is possibly adequate to support future Mineral Resource estimation but will be reassessed if required. Ballymore drilling: drill core was logged for lithology, structure, alteration, mineralisation, and veining, while percussion chips were logged for lithology, alteration and mineralisation, which is deemed to be appropriate for the style of mineralisation and the lithologies encountered. All core was photographed. Logging information is adequate to support Mineral Resource estimation. Information to support geotechnical studies is available.
	Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.	Logging of core is mostly qualitative, except for some semi-quantitative logging of sulphide content, quartz veining, RQD, and geotechnical parameters.
	The total length and percentage of the relevant intersections logged.	Geological logs were completed for all drilled intervals.
SUB-SAMPLING TECHNIQUES AND SAMPLE PREPARATION	If core, whether cut or sawn and whether quarter, half or all core taken.	No information is available on moisture content of non-core samples or how the drilled material was sampled for historic drilling. No details of the laboratory preparation of samples were recorded for historic drilling. It is assumed that sample preparation methods used by all commercial laboratories followed the basic steps of drying, crushing, and pulverising, but details of the amount of the sample crushed and pulverised are not known. Therefore, it is not possible to assess the quality and appropriateness of the sample preparation techniques. Ballymore drilling: Ballymore cut core samples in half or quarter using a diamond saw and where appropriate used geological contacts or mineralisation to define sample intervals.
	If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.	No information is available on moisture content of non-core samples or how the drilled material was sampled for historic drilling. Ballymore drilling: Sampling was collected via cone splitting; RC drilling was stopped when unacceptable levels of water was encountered.
	For all sample types, the nature, quality, and appropriateness of the sample preparation technique.	No details of the laboratory preparation of samples were recorded for historic drilling. It is assumed that sample preparation methods used by all commercial laboratories followed the basic steps of drying, crushing, and pulverising, but details of the amount of the sample crushed and pulverised are not known. Therefore, it is not possible to assess the quality and appropriateness of the sample preparation techniques. Ballymore diamond drilling: Half core was submitted to the laboratory, generally 2 – 3 kg per sample. All of the core was dried, crushed to -6 mm, then pulverised to 85% - 75 µm. This method is considered appropriate for mineralisation that may have visible gold mineralisation. Ballymore RC drilling: RC samples were split using a rig-mounted cone splitter on 1m intervals to obtain a sample for assay, of approximate weight 3 – 5kg. Samples were dried, crushed to -6 mm, then pulverised to 85% - 75 µm. This method is considered appropriate for mineralisation that may have visible gold mineralisation.

personal use only

CRITERIA	JORC Code Explanation	Commentary
	Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.	No information has been recorded that documents quality control procedures adopted for all sub-sampling stages to maximise representivity of samples for historic drilling. Ballymore diamond drilling: Drill core samples of cut core were consistently taken from the same side of the orientation line on the core to maintain consistency. All of the sample was crushed and pulverised to maximise sample representativity. Pulverised samples were tested for compliance to grinding specifications at the rate of 1 in 40. Ballymore RC drilling: RC samples were split using a rig-mounted cone splitter on 1m intervals to obtain a sample for assay, of approximate weight 3 – 5kg. All of the sample was crushed and pulverised to maximise sample representativity. Pulverised samples were tested for compliance to grinding specifications at the rate of 1 in 40.
	Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.	No information has been recorded for historic drilling that documents measures taken to ensure that the sampling is representative of the in situ material collected. Ballymore diamond drilling: QA/QC procedures included the insertion of quarter core field duplicates at the insertion rate of 1 in 20 samples. Field blanks were also submitted to the laboratory. Ballymore RC drilling: QA/QC procedures included the insertion of field duplicates at the insertion rate of 1 in 20 samples. Field blanks were also submitted to the laboratory.
	Whether sample sizes are appropriate to the grain size of the material being sampled.	No formal assessment has been undertaken to quantify the appropriate sample size required for good quality determination of gold or base metal content, given the nature of the gold and base metal mineralisation.
QUALITY OF ASSAY DATA AND LABORATORY TESTS	The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.	No information has been recorded that documents the nature, quality, and appropriateness of assaying methods used for any of the drilling programs. Ballymore 2022 drilling: ALS Townsville Laboratory was used. Gold assays were analysed with a 50 g charge used for fire assay with an ICP-AES determination. Over range gold samples (>10 ppm) were re-analysed by fire assay and gravimetric finish. In addition, a 0.25 g charge was taken for analysis for 48 elements (Ag, Al, As, Ba, Be, Bi, Ca, Cd, Ce, Co, Cr, Cs, Cu, Fe, Ga, Ge, Hf, In, K, La, Li, Mg, Mn, Mo, Na, Nb, Ni, P, Pb, Rb, Re, S, Sb, Sc, Se, Sn, Sr, Ta, Te, Th, Ti, Tl, U, V, W, Y, Zn, Zr) utilising a four-acid digest with an ICP-MS determination. Any over range Cu, Pb or Zn (>10000 ppm) and Ag (>100 ppm) was re-analysed using a standard Ore Grade method utilising a four-acid digest producing a volumetrically precise digest analysed with an ICP-AES finish for high detection limits. The fire assay method for gold using either a 30 g or 50 g charge is an appropriate assay method and is normally considered a total assay method, except where gold grain size is very coarse. Ballymore 2025 & 2026 drilling: Intertek Townsville Laboratory was used. Gold assays were analysed with a 50 g charge used for fire assay with an ICP-AES determination. In addition, a 0.25 g charge was taken for analysis for 48 elements (Ag, Al, As, Ba, Be, Bi, Ca, Cd, Ce, Co, Cr, Cs, Cu, Fe, Ga, Ge, Hf, In, K, La, Li, Mg, Mn, Mo, Na, Nb, Ni, P, Pb, Rb, Re, S, Sb, Sc, Se, Sn, Sr, Ta, Te, Th, Ti, Tl, U, V, W, Y, Zn, Zr) utilising a four-acid digest with an ICP-MS determination. Any over range Cu, Pb or Zn (>10000 ppm) was re-analysed using a standard Ore Grade method utilising a four-acid digest producing a volumetrically precise digest analysed with an ICP-AES finish for high detection limits. The fire assay method for gold using either a 30 g or 50 g charge is an appropriate assay method and is normally considered a total assay method, except where gold grain size is very coarse. Ballymore soil, stream and rock chip samples were analysed at ALS Townsville using a multi-element suite by aqua regia digestion and ICP-MS finish. For most elements, this is considered as a total analysis. Gold was analysed with a 50 g charge used for fire assay with an ICP-AES determination. Normally the gold analysis would be considered a total analysis.

personal use only

CRITERIA	JORC Code Explanation	Commentary
	For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.	Ballymore used a pXRF instrument for its Ruddygore, Maniopota and Torpy's Crooked Creek soil programs. Soil samples were sieved to -80# and a 150 g sample was collected. Samples were analysed using an Olympus Vanta C Series (TL-WN725N) portable XRF analyser. Samples were analysed for Ag, As, Bi, Ca, Cd, Cl, Co, Cr, Cu, Fe, Hg, K, Mn, Mo, Nb, Ni, P, Pb, Rb, S, Sb, Se, Sn, Sr, Th, Ti, Tl, U, V, W, Y, Zn, Zr. The pXRF instrument is calibrated and serviced annually, with daily calibration completed as a minimum. At the start of each sampling session, standards are analysed. Sample material remains in storage for analytical re-assay as required. The Ruddygore Dipole-Dipole IP survey completed at Ruddygore prospect by Ballymore in September-October 2021 was undertaken using a GDD Model TX 4 20A/5000W/2400V transmitter and Smartem 16 Channel receiver. Seven 3km lines were surveyed. The northern most traverse was collected using a 50m Dipole-Dipole (Tx & Rx) configuration to an "n" level of n=10. The remaining six traverses were collected using a 100m Dipole-Dipole (Tx & Rx) configuration to an "n" level of n=8. The data is of high quality with strong signal levels resulting in coherent decays and good repeatability. MagSpec flew an airborne magnetic and radiometric survey in 2021 on behalf of Ballymore at 50m line spacing and 50m flight height. Two areas were collected: Chillagoe North and Chillagoe South. The Maniopota EM Survey was completed with the SkyTEM helicopter time-domain AEM system. The SkyTEM312HP system uniquely acquires at transmitter frequencies as low as 12.5Hz, using a high-power square wave form for enhanced resolution, a wide transmitter pulse width for greater target energisation, and long transmitter off times for imaging deep and conductive targets. Ballymore Gravity Survey completed in 2026 by Daishsat and were acquired using the company's Scintrex CG-5 Autograv gravity meters. A Standard Deviation (SD) of around 0.025 milliGals is typical final accuracy of the gravity observations using our proposed equipment and techniques.
	Nature of quality control procedures adopted (e.g., standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e., lack of bias) and precision have been established.	No details of the use of standards or certified reference materials have been reported for historic work. Ballymore drilling: In addition to blanks and field duplicates, commercial CRMs of low grade to high grade gold ore material were prepared and certified for Au, Ag, Cu, Pb and Zn by Ore Research & Exploration Services Pty Ltd. These were incorporated into the sampling stream to achieve an overall insertion rate of 1 duplicate, blank or CRM for every 10 core samples. When undertaking pXRF surveys, Ballymore applied its QA/QC procedures and checked standards prior to commencing surveying on a daily basis as well as routinely testing for drift during the day by regularly checking standards.
VERIFICATION OF SAMPLING AND ASSAYING	The verification of significant intersections by either independent or alternative company personnel.	It has not been possible to independently verify significant intersections to date.
	The use of twinned holes.	There has been no use of twinned holes to date.
	Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.	Ballymore has collated and created a digital database of previous exploration completed at the Project. Ballymore drilling: Primary logging data was recorded digitally onto electronic spread sheets and validated against code tables by the logging geologist. Primary analytical data was received electronically in csv file format and imported directly into an electronic assay register spread sheet. Data validation was conducted by comparing the spreadsheet data against the Certificate of Analysis supplied as a secured pdf file by the laboratory.
	Discuss any adjustment to assay data.	No adjustments to assay data have been made.

personal use only

CRITERIA	JORC Code Explanation	Commentary
LOCATION OF DATA POINTS	Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.	No details of the accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys) is recorded. Drillhole collar locations were typically based on local grids and the accuracy of drill collars has not been verified to date. Ballymore surface geochemical sampling is surveyed using a handheld GPS with a location error of +/- 5m. Ballymore surface drilling: Drillhole collar locations were initially set out (and reported) using a handheld GPS with a location error of +/- 5m. All holes were subsequently surveyed by contract surveyor to a sub-metre accuracy, with data supplied electronically as spreadsheets and pdf files. The azimuth and dip at the start of the hole was recorded using a line of sight Suunto compass and Suunto clinometer by the site geologist. The orientation and dip of drillholes are measured with downhole surveys @ 15 m, 30 m, then every 30 m using a REFLEX single/multi-shot survey tool. End of hole surveys were also taken for each hole. At hole completion, holes were gyro surveyed. Ballymore Maniopota AEM Survey: The SkyTEM survey was completed with all data located via on-board DGPS. Ballymore Gravity Survey: The Daishsat survey was completed with all data located via a Leica GX1230 Real-Time- Kinematic (RTK) GNSS giving a set out accuracy better than 5cm (where terrain allows) in micro gravity surveys and regional surveys were located via autonomous GNSS positioning is used to set out the stations.
	Specification of the grid system used.	The co-ordinate system used is MGA94 zone 55 Datum.
	Quality and adequacy of topographic control.	Quality of the surface topographic control data is poor and is currently reliant on public domain data.
DATA SPACING AND DISTRIBUTION	Data spacing for reporting of Exploration Results.	Drilling: There is a small amount of drilling to date and the spacing of drillhole data is variable. Ballymore Maniopota AEM Survey: The AEM survey was flown at 200m spacing in a NE-SW orientation. Ruddygore Gravity Survey: The survey comprised a regional survey on a notional 500m grid across the survey area. In addition, several priority prospects underwent detailed surveying at a notional station spacing of 50m 100m at MAN03, Eleventh and Maniopota and at a station spacing of 50m x 50m at Armada East. At Torpy's a detailed survey was completed at a notional 25m x 25m spacing over the mine area within a greater area surveyed at 50m x 50m.
	Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.	There are no Mineral Resources or Ore Reserves. There is insufficient drill spacing to establish the degree of geological and grade continuity appropriate for Mineral Resource and Ore Reserve estimation.
	Whether sample compositing has been applied.	No sample compositing was carried out on site. For reporting purposes, some drill hole assay results have been composited together to report contiguous zones of mineralisation.
ORIENTATION OF DATA IN RELATION TO GEOLOGICAL STRUCTURE	Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.	The majority of previous drill holes were drilled vertically and are not considered to be oriented appropriately to drill across mineralisation. Further drilling is required to establish the optimal orientation of drilling at Ruddygore, Maniopota, and Torpy's Crooked Creek. Potential exists for sampling bias to have been introduced in the drilling completed to date due to the vertical nature of the drilling. Ballymore drill holes completed at Ruddygore were inclined holes, approximately perpendicular to the strike of the main mineralised zone which is considered appropriate. Some holes are also twinned. Nevertheless, to date Ballymore has only drilled six holes and further drilling is required.

personal use only

CRITERIA	JORC Code Explanation	Commentary
		Ballymore drill holes completed at Torpy's were drilled targeting structural targets at a high angle, which is considered appropriate for this target.
	If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.	It is possible there could be sampling bias due to the orientation of drilling but doe to the lack of drilling to date this has not been ascertained.
SAMPLE SECURITY	The measures taken to ensure sample security.	No chain of custody is documented for previous drilling. For Ballymore sampling programs, all work was supervised by company staff. Samples were double bagged, palletised and shrink wrapped at the core shed before dispatch to the laboratory.
AUDITS OR REVIEWS	The results of any audits or reviews of sampling techniques and data.	Ballymore programs: Internal auditing procedures and reviews were regularly undertaken on sampling techniques, standard operating procedures, and laboratory processes. Derisk has completed a review of the work Ballymore has undertaken.

Reporting of Exploration Results

CRITERIA	JORC Code explanation	Commentary
MINERAL TENEMENT AND LAND TENURE STATUS	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	The Project tenements comprise EPM 14015, EPM 15047, EPM 15053, and EPM 27840. All licences are 100% held by Ballymore Resources Limited.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	All tenements are in good standing.
EXPLORATION DONE BY OTHER PARTIES	Acknowledgment and appraisal of exploration by other parties.	The Ruddygore Mine was mined from 1896 – 1909 by open cut and shaft access to underground. The mine yielded 1,450 tons of copper from 32,750 tons of handpicked ore. The Torpy's Crooked Creek mine operated from 1904 – 1907 and 1912 – 1914. Production figures have not been located for 1904 – 1907 but from 1912 – 1914 the mine yielded 6,000 tons of ore for 84,000 oz silver and 920 tons of lead. The Maniopota mine was mined for lead, zinc, and silver. No production records have been found for the area but it hosts a series of small pits over 1 km strike length. Numerous exploration permits and mining leases have been held over parts and/or all of the Project area. Previous exploration has included geological mapping, soil and rock chip geochemical sampling, airborne and ground geophysics, plus RC and diamond drilling. Major programs included:

personal use only

CRITERIA	JORC Code explanation	Commentary
		▪ Mount Isa Mines (1959 – 1961) completed magnetic and EM surveys and diamond drilling (9 diamond drillholes for 655 m) at Ruddygore. ▪ Kennecott Exploration Australia (1965 – 1967) completed a geochemical survey over Ruddygore. ▪ Mines Exploration (1966 – 1971) completed geological mapping and channel sampling and drilling (3 holes for 598 m) at Maniopota. ▪ Cyprus Mines Corporation (1969 – 1970) completed mapping, geochemical surveys, IP and magnetic surveys and diamond drilling at Ruddygore (two holes for 182.88 m). ▪ LE Nickel (1976 – 1977) completed mapping and two diamond drillholes at Torpy's Crooked Creek for 421.6 m. ▪ BP Mining Development Australia (1977 – 1978) completed airborne and ground magnetics and radiometrics surveys. ▪ AOG Minerals (1980 – 1982) completed EIP survey, rock and soil sampling, costeaning and drilling at Ruddygore (four drillholes for 469.1 m). ▪ Cyprus Mines Corporation (1986 – 1989) completed open hole percussion drilling around Ruddygore pit (11 holes for 324 m). ▪ Dominion Mining Limited/Stuart Foster (1991 – 1993) completed a ground magnetic survey, channel sampling at Maniopota and RC drilling (11 holes for 461 m). ▪ CRA Exploration (1993 – 1995) completed an EM survey over the Torpy's Mine and drilled 12 holes for 1,027 m at Metal Creek.
GEOLOGY	Deposit type, geological setting, and style of mineralisation.	The Chillagoe District is situated within the Middle Palaeozoic Hodgkinson Province which is the northernmost part of the Tasmanides in eastern Australia. Ballymore considers that the Ruddygore Project is prospective for large tonnage multi-element deposits including (a) copper-gold porphyry deposits e.g., Ruddygore (b) copper-gold-lead-zinc skarn deposits e.g., Red Dome, Mungana, Maniopota (c) sediment-hosted massive sulphide lead-zinc-silver e.g., Torpy's Crooked Creek, and (d) gold IRGS deposits e.g., Kidston.
DRILL HOLE INFORMATION	A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: – Easting and northing of the drill hole collar. – Elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar. – Dip and azimuth of the hole. – Down hole length and interception depth. – Hole length.	Refer to Appendix 2.

personal use only

CRITERIA	JORC Code explanation	Commentary
	If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	Refer to Appendix 2.
DATA AGGREGATION METHODS	In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g., cutting of high grades) and cut-off grades are usually Material and should be stated.	The mineralised drill intersections are reported as downhole intervals and were not converted to true widths. True widths may be up to 50% less than drill intersections pending confirmation of mineralisation geometry. No capping of high grades was performed in the aggregation process.
	Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.	Ballymore drill intercepts reported as Exploration Results were calculated using different criteria depending on the nature of the mineralisation. For base metal mineralisation 0.1%, 0.5%, 1.0%, 5.0% and 10.0% Cu, Pb or Zn have been applied for reporting. Silver intersections were generally reported at 10g/t and 100 g/t Ag.
	The assumptions used for any reporting of metal equivalent values should be clearly stated	No metal equivalent results have been quoted. For all previous exploration results refer to ASX releases. The dominant composite length is 1m. No top-cut or capping was applied.
RELATIONSHIP BETWEEN MINERALISATION WIDTHS AND INTERCEPT LENGTHS	These relationships are particularly important in the reporting of Exploration Results.	Previous drilling was planned on local grid lines and most drill holes were vertical. The limited drilling to date means the relationships between mineralisation widths and intercept lengths is poorly understood.
	If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.	Ruddygore prospect is a porphyry copper style with veining and brecciation occurring in fine- and medium-grained intrusives that strike north-northwest and are steeply dipping as well as in sub-horizontal fractures. Almost all holes drilled to date were vertical holes, which is not optimal for testing this style of deposit. Maniopota prospect is Cu-Pb-Zn-Ag-Au mineralisation associated with skarn alteration along the contact of the Almaden Granodiorite and the Chillagoe Formation, which varies from north-south to northwest-southeast, typically dipping moderately towards the southwest. All except 1 of the 14 holes have been drilled towards the northeast, which is approximately perpendicular to the target. The orientation and extent of the Torpy's Crooked Creek Pb-Zn-Ag deposit is poorly understood. To date, two historical and 31 current BMR drill holes and have been completed. The results to date suggest that the drilling orientation is suitable for the style and orientation of mineralisation.
	If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g., 'down hole length, true width not known').	The mineralised intercepts generally intersect the interpreted dip of the mineralisation at a high angle but are not true widths.
DIAGRAMS	Appropriate maps and sections (with scales) and tabulations of intercepts should be included	Refer to figures contained within this report.

personal use only

CRITERIA	JORC Code explanation	Commentary
	for any significant discovery being reported These should include but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	
BALANCED REPORTING	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	Balanced reporting of Exploration Results is presented within this report.
OTHER SUBSTANTIVE EXPLORATION DATA	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	The Project includes a large amount of exploration data collected by previous companies, including regional stream sediment geochemical data, soil sample and rock chip data, geological mapping data, drilling data, geophysical survey data, and costean data. Much of this data has been captured and validated into a GIS database. Previous mining has been limited and involved very selective mining and hand sorting. No systematic data has been collected to date to assess metallurgy and mining parameters relevant to a modern operation.
FURTHER WORK	The nature and scale of planned further work (e.g., tests for lateral extensions or depth extensions or large-scale step-out drilling).	Ballymore plans to conduct surface geological mapping and geochemistry, ground geophysics and drilling across various high-priority target areas over the next two years.
	Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.	Refer to figures contained within this report.

personal use only

APPENDIX 2. TORPY'S DRILL COLLAR AND SURVEY INFORMATION

Company	Target	HoleID	Hole Type	East (MGA)	North (MGA)	RL	Depth (m)	Dip (°)	Azimuth (° MGA)	Licence	Year
Ballymore	Torpy's	BTPRC010*	Reverse Circulation	258240.685	8083174.398	519.879	180	-60	320	EPM 14015	2026
Ballymore	Torpy's	BTPRC011*	Reverse Circulation	258240.058	8083177.073	519.825	212	-61	335	EPM 14015	2026
Ballymore	Torpy's	BTPRC012*	Reverse Circulation	258223.616	8083220.517	517.744	152	-61	332	EPM 14015	2026
Ballymore	Torpy's	BTPRC013*	Reverse Circulation	258232.753	8083223.653	517.804	96	-61	334	EPM 14015	2026
Ballymore	Torpy's	BTPRC014*	Reverse Circulation	258211.773	8083212.994	517.466	150	-61	333	EPM 14015	2026
Ballymore	Torpy's	BTPRC015*	Reverse Circulation	258236.302	8083266.049	518.097	72	-60	346	EPM 14015	2026
Ballymore	Torpy's	BTPRC016*	Reverse Circulation	258240.757	8083227.986	517.585	158	-60	333	EPM 14015	2026
Ballymore	Torpy's	BTPRC017*	Reverse Circulation	258192.789	8083246.807	519.568	116	-61	334	EPM 14015	2026
Ballymore	Torpy's	BTPRC018*	Reverse Circulation	258207.234	8083242.888	519	98	-61	334	EPM 14015	2026
Ballymore	Torpy's	BTPRC019*	Reverse Circulation	258221.188	8083245.432	518.681	60	-60	321	EPM 14015	2026
Ballymore	Torpy's	BTPRC020*	Reverse Circulation	258176.36	8083276.907	521.349	98	-62	335	EPM 14015	2026
Ballymore	Torpy's	BTPRC021*	Reverse Circulation	258185.247	8083276.833	520.827	80	-81	335	EPM 14015	2026
Ballymore	Torpy's	BTPRC022*	Reverse Circulation	258197.699	8083285.135	520.412	36	-90	0	EPM 14015	2026
Ballymore	Torpy's	BTPRC023*	Reverse Circulation	258235.222	8083206.005	518.084	102	-61	333	EPM 14015	2026
Ballymore	Torpy's	BTPRC024*	Reverse Circulation	258249.349	8083177.429	518.979	152	-60	335	EPM 14015	2026
Ballymore	Torpy's	BTPRC025*	Reverse Circulation	258263.645	8083193.335	517.063	182	-60	334	EPM 14015	2026

personal use only

Company	Target	HoleID	Hole Type	East (MGA)	North (MGA)	RL	Depth (m)	Dip (°)	Azimuth (° MGA)	Licence	Year
Ballymore	Torpy's	BTPRC026*	Reverse Circulation	258222.27	8083200.676	518.149	163	-60	331	EPM 14015	2026
Ballymore	Little Torpy's	BTPRC027*	Reverse Circulation	257987.022	8082666.071	500.489	92	-55	70	EPM 14015	2026
Ballymore	Little Torpy's	BTPRC028*	Reverse Circulation	258005.537	8082709.207	505.407	98	-69	139	EPM 14015	2026
Ballymore	Little Torpy's	BTPRC029*	Reverse Circulation	258054.378	8082644.485	503.893	110	-65	326	EPM 14015	2026
Ballymore	Little Torpy's	BTPRC030*	Reverse Circulation	258044.814	8082677.149	505.705	86	-65	245	EPM 14015	2026
Ballymore	Little Torpy's	BTPRC031*	Reverse Circulation	258047.622	8082678.188	505.662	116	-75	234	EPM 14015	2026

* Drill hole collar location picked up by DGPS

personal use only

APPENDIX 3. TORPY'S DRILLING HIGHLIGHTS

Cut-Off	Hole	From	To	Interval	Ag g/t	Pb %	Zn %	Cu %	In g/t	Au g/t
0.1% Pb	BTPRC010	76	90	14	76.6	3.43	2.32	0.03	3.74	0.03
1.0% Pb	**Including**	**79**	**88**	**9**	**117.2**	**5.26**	**3.54**	**0.04**	**5.62**	**0.05**
10.0% Pb	Including	79	82	3	249.6	12.19	6.05	0.07	8.32	0.07
5.0% Pb	And	87	88	1	189.1	6.25	8.45	0.05	11.03	0.09
1.0% Pb	BTPRC011	80	81	1	51.0	3.27	0.88	0.01	1.74	0.05
0.1% Pb	**BTPRC011**	**105**	**134**	**29**	**71.3**	**3.64**	**2.19**	**0.03**	**7.11**	**0.01**
1.0% Pb	**Including**	**107**	**112**	**5**	**126.1**	**8.57**	**2.63**	**0.02**	**5.08**	**0.02**
1.0% Pb	**And**	**120**	**133**	**13**	**104.9**	**4.59**	**3.57**	**0.06**	**13.27**	**0.02**
10.0% Pb	Including	125	126	1	199.9	11.64	2.54	0.01	10.06	0.03
10.0% Pb	**And**	**129**	**130**	**1**	**231.7**	**11.27**	**8.44**	**0.01**	**32.32**	**0.06**
0.5% Pb	BTPRC012	6	10	4	85.3	4.43	0.60	0.03	1.56	0.02
1.0% Pb	Including	6	8	2	163.1	8.29	0.66	0.05	2.91	0.05
0.1% Pb	BTPRC012	38	58	20	43.0	1.80	1.05	0.05	1.08	0.03
5.0% Pb	Including	39	40	1	137.1	7.89	7.77	0.05	4.96	0.01
0.5% Pb	And	54	58	4	130.9	4.78	0.64	0.17	1.40	0.03
1.0% Pb	Including	54	56	2	247.8	9.16	0.97	0.28	1.66	0.07
10.0% Pb	Including	55	56	1	355.2	14.80	1.05	0.33	1.89	0.10
0.1% Pb	**BTPRC013**	**44**	**51**	**7**	**170.0**	**7.60**	**3.27**	**0.00**	**2.97**	**0.03**
1.0% Pb	**Including**	**45**	**48**	**3**	**391.1**	**17.45**	**7.43**	**0.00**	**6.73**	**0.08**
10.0% Pb	**Including**	**46**	**48**	**2**	**580.4**	**25.88**	**10.08**	**0.00**	**8.79**	**0.12**
0.1% Zn	BTPRC014	6	19	13	0.8	0.00	0.13	0.00	0.16	0.00
0.1% Zn	BTPRC014	24	57	33	0.4	0.01	0.19	0.00	0.27	0.00
0.1% Zn	BTPRC014	68	83	15	0.3	0.02	0.53	0.00	0.09	0.01
0.5% Zn	Including	74	82	8	0.4	0.01	0.73	0.00	0.11	0.02
1.0% Zn	Including	74	75	1	0.3	0.02	1.65	0.00	0.07	0.01
0.1% Zn	BTPRC014	91	92	1	0.5	0.01	0.13	0.01	0.16	<0.01

personal use only

Cut-Off	Hole	From	To	Interval	Ag g/t	Pb %	Zn %	Cu %	In g/t	Au g/t
0.1% Zn	BTPRC014	115	117	2	0.8	0.01	0.13	0.01	0.29	<0.01
0.1% Pb	BTPRC015	0	1	1	3.2	0.14	0.23	0.01	0.53	<0.01
0.1% Pb	BTPRC015	14	18	4	17.6	0.87	0.32	0.05	0.35	0.00
1.0% Pb	Including	15	16	1	28.2	1.61	0.40	0.09	0.56	0.01
0.1% Pb	BTPRC015	36	37	1	26.0	0.17	0.76	0.36	1.14	0.01
0.1% Zn	BTPRC016	19	21	2	0.6	0.00	0.15	0.00	0.32	<0.01
0.1% Zn	BTPRC016	36	45	9	1.2	0.03	0.21	0.00	0.14	0.01
1.0% Zn	BTPRC016	63	64	1	21.6	0.56	1.65	0.01	2.78	0.01
0.1% Zn	BTPRC016	98	104	6	0.2	0.01	0.34	0.00	0.06	0.00
0.1% Pb	**BTPRC017**	**49**	**59**	**10**	**90.3**	**8.72**	**9.08**	**0.07**	**2.41**	**0.02**
0.5% Pb	**Including**	**49**	**57**	**8**	**111.7**	**10.82**	**11.27**	**0.09**	**2.93**	**0.03**
10.0% Pb	**Including**	**49**	**56**	**7**	**125.8**	**12.23**	**12.77**	**0.10**	**3.28**	**0.03**
10.0% Pb	**Including**	**49**	**50**	**1**	**118.2**	**16.65**	**19.20**	**0.18**	**3.52**	**0.11**
10.0% Pb	**And**	**52**	**56**	**4**	**179.4**	**15.70**	**15.99**	**0.12**	**4.37**	**0.02**
0.1% Pb	**BTPRC018**	**27**	**32**	**5**	**149.4**	**6.92**	**9.09**	**0.06**	**3.55**	**0.04**
1.0% Pb	**Including**	**27**	**30**	**3**	**238.7**	**11.33**	**14.15**	**0.09**	**5.01**	**0.06**
10.0% Pb	**Including**	**27**	**29**	**2**	**334.0**	**15.61**	**19.08**	**0.13**	**6.42**	**0.08**
0.1% Pb	**BTPRC018**	**37**	**49**	**12**	**97.6**	**5.40**	**3.60**	**0.01**	**2.77**	**0.01**
1.0% Pb	**Including**	**37**	**41**	**4**	**284.4**	**15.79**	**10.40**	**0.02**	**7.98**	**0.04**
10.0% Pb	**Including**	**38**	**41**	**3**	**360.4**	**20.26**	**13.37**	**0.02**	**10.17**	**0.05**
0.1% Pb	BTPRC018	56	62	6	43.8	3.54	4.17	0.02	1.01	0.00
1.0% Pb	Including	56	58	2	123.9	10.14	11.30	0.04	2.88	0.01
10.0% Pb	Including	57	58	1	186.0	13.63	15.95	0.07	3.82	0.02
0.1% Pb	BTPRC019	9	31	22	29.8	1.41	0.98	0.02	1.13	0.03
0.5% Pb	Including	27	30	3	119.6	5.72	4.46	0.09	5.22	0.09
1.0% Pb	Including	27	29	2	168.3	8.15	6.31	0.11	7.38	0.13
10.0% Pb	Including	28	29	1	276.2	11.60	7.96	0.21	8.52	0.06
0.1% Pb	**BTPRC019**	**52**	**60**	**8**	**57.1**	**3.71**	**3.30**	**0.02**	**3.03**	**0.02**

personal use only

Cut-Off	Hole	From	To	Interval	Ag g/t	Pb %	Zn %	Cu %	In g/t	Au g/t
1.0% Pb	**Including**	**55**	**60**	**5**	**88.2**	**5.79**	**5.11**	**0.02**	**4.60**	**0.03**
10.0% Pb	**Including**	**55**	**56**	**1**	**195.5**	**17.66**	**12.83**	**0.07**	**11.09**	**0.03**
10.0% Pb	**And**	**59**	**60**	**1**	**226.9**	**10.22**	**11.04**	**0.04**	**10.51**	**0.08**
0.1% Pb	BTPRC020	7	24	17	11.0	0.30	0.16	0.00	0.09	0.00
0.5% Pb	**Including**	**14**	**16**	**2**	**63.0**	**1.04**	**0.26**	**0.01**	**0.15**	**0.00**
1.0% Pb	**Including**	**15**	**16**	**1**	**111.8**	**1.33**	**0.13**	**0.01**	**0.07**	**0.01**
0.1% Zn	BTPRC021	0	41	41	2.6	0.03	0.19	0.00	0.13	0.00
5 g/t Ag	BTPRC021	0	3	3	7.7	0.04	0.34	0.00	0.07	<0.01
10 g/t Ag	Including	1	2	1	10.3	0.02	0.53	0.00	0.07	<0.01
10 g/t Ag	BTPRC021	22	23	1	34.2	0.67	0.52	0.01	0.32	<0.01
0.1% Zn	BTPRC021	49	62	13	0.3	0.01	0.16	0.00	0.09	0.00
0.1% Pb	BTPRC022	0	8	8	8.6	0.30	0.29	0.00	0.32	-0.01
0.5% Pb	Including	5	6	1	29.6	0.79	0.26	0.01	0.59	-0.01
0.1% Pb	**BTPRC022**	**12**	**28**	**16**	**36.5**	**1.31**	**2.38**	**0.02**	**2.48**	**0.03**
0.5% Pb	**Including**	**12**	**17**	**5**	**61.0**	**2.32**	**2.89**	**0.02**	**1.60**	**0.06**
1.0% Pb	**Including**	**16**	**17**	**1**	**207.7**	**9.94**	**12.52**	**0.02**	**5.31**	**0.17**
1.0% Pb	**And**	**21**	**23**	**2**	**105.9**	**3.84**	**9.56**	**0.08**	**14.50**	**0.07**
0.1% Pb	BTPRC023	26	29	3	0.8	0.11	0.30	0.01	0.47	0.00
0.1% Pb	**BTPRC023**	**54**	**65**	**11**	**49.1**	**1.06**	**0.74**	**0.09**	**1.58**	**0.02**
0.5% Pb	**Including**	**55**	**59**	**4**	**127.1**	**2.61**	**1.52**	**0.22**	**3.84**	**0.05**
1.0% Pb	**Including**	**55**	**58**	**3**	**162.7**	**3.26**	**1.75**	**0.27**	**4.73**	**0.06**
0.1% Pb	BTPRC023	69	70	1	4.2	0.18	0.21	0.00	0.23	-0.01
0.1% Pb	BTPRC023	99	100	1	8.8	0.24	0.27	0.04	0.48	0.13
0.1% Pb	BTPRC024	87	96	9	14.6	0.44	0.28	0.03	0.51	0.03
0.5% Pb	Including	89	91	2	26.5	0.79	0.11	0.03	0.58	0.05
1.0% Pb	And	94	95	1	36.5	1.45	0.69	0.04	1.20	0.01
0.1% Pb	BTPRC024	104	108	4	8.3	0.30	0.23	0.01	0.66	0.00
0.5% Pb	Including	104	105	1	18.4	0.80	0.59	0.01	1.40	0.01

personal use only

Cut-Off	Hole	From	To	Interval	Ag g/t	Pb %	Zn %	Cu %	In g/t	Au g/t
0.1% Zn	BTPRC025	56	57	1	0.8	0.05	0.11	0.00	0.28	0.01
0.1% Zn	BTPRC025	80	81	1	0.9	0.03	0.17	0.01	0.32	-0.01
0.1% Zn	BTPRC025	120	121	1	1.2	0.03	0.14	0.01	1.18	-0.01
0.1% Zn	BTPRC026	13	28	15	0.4	0.00	0.14	0.00	0.13	0.00
0.1% Zn	BTPRC026	37	46	9	0.4	0.01	0.16	0.00	0.10	0.01
0.1% Zn	BTPRC026	63	65	2	0.6	0.00	0.12	0.00	0.16	0.03
0.1% Zn	BTPRC026	70	71	1	1.3	0.01	0.12	0.01	0.50	-0.01
0.1% Zn	BTPRC026	84	93	9	1.4	0.02	0.26	0.01	0.22	0.11
0.5% Zn	Including	86	87	1	5.5	0.10	0.73	0.01	0.60	0.02

personal use only